

PCC.II/DEC. 93 (XV-10)¹

FIVE RNSS DRAFT NEW RECOMMENDATIONS

The XV Meeting of the Permanent Consultative Committee II: Radiocommunications including Broadcasting,

DECIDES:

To instruct the Executive Secretary:

1. To send the Member States of CITELE the document CCP.II-RADIO/doc.2209/10, which provides a description of the status of five draft New Recommendations related to the Radionavigation Satellite Service (RNSS) that were considered in the ITU-R and sent to the 2012 ITU Radiocommunications Assembly
2. To invite the Member States of CITELE to support the proposal of guidelines, to be developed in the framework of this Permanent Consultative Committee, to support the approval of the above mentioned draft Recommendations for presentation to the ITU Radiocommunications Assembly of 2012.

ANNEX TO DECISION PCC.II/DEC. 93 (XV-10)

PACKAGE OF FIVE RNSS RECOMMENDATIONS

Following are the set of five RNSS Draft New Recommendations that were discussed at the July 2010 Study Group 4 meeting:

- Draft New Recommendation ITU-R M.[Char-Rx3] “Characteristics and protection criteria for receiving earth stations in the radionavigation-satellite service (space-to-Earth) operating in the band 1 164-1 215 MHz” (see ITU-R Document 4/100).
- Draft New Recommendation ITU-R M.[1088_New] “Characteristics and protection criteria for receiving earth stations in the radionavigation-satellite service (space-to-Earth) operating in the band 1 215-1 300 MHz” (see ITU-R Document 4/97).
- Draft New Recommendation ITU-R M.[1477_New] “Characteristics and protection criteria for receiving earth stations in the radionavigation-satellite service (space-to-Earth) and receivers in the aeronautical radionavigation service operating in the band 1 559-1 610 MHz” (see ITU-R Document 4/98).
- Draft New Recommendation ITU-R M.[1479_New] “Characteristics, performance requirements and protection criteria for receiving stations of the radionavigation-satellite service (space-to-space) operating in the frequency bands 1 164-1 215 MHz, 1 215-1 300 MHz and 1 559-1 610 MHz” (see ITU-R Document 4/99).
- Draft New Recommendation ITU-R M.[RNSS_Guide] “Guidance on ITU-R Recommendations related to systems and networks in the radionavigation-satellite service operating in the frequency bands 1 164-1 215 MHz, 1 215-1 300 MHz, 1 559-1 610 MHz, 5 000-5 010 MHz and 5 010-5 030 MHz” (see ITU-R Document 4/96).

¹ CCP.II-RADIO/doc. 2331/10 rev.2

These Draft New Recommendations may be found at the following ITU-R website:
<http://www.itu.int/md/R07-SG04-C/en>.